

Box 1246 2876 Culver Ave. Dayton, Ohio 45401 Telephone (513) 296-0330

Operating Instructions

For Model 222 A, C

185B

280 ZZZAP

MIDWAY

	SL?				START 2			SR2			5 V		
LLP	SL1	¥ SL5	8T.3	LRP	,	X START 1	ALP	SRI	sas	SR3	ARP	ON	OFF
· x	x	¤ \$L4	1	¥	ĸ	x	¥	*	x \$R4	x			
	SL6	×	SL7			COIN		S A 6	×	\$A 7		PO	WER
	X.		x			×		×		x	×	ÓN	OFF

- Insert 185B card into program "B" connector, number side up. 1.
- Insert 222A card into program "A" connector, number side up. 2.
- Insert 222C card into test fixture with number side up. 3.
- Insert GAME MOTHER BOARD into 222C card. (CAUTION: Align edgeboard 4. to connector)
- 5. Connect two remote connectors on 222A card to game control board with red dot showing.
- 6. Connect 8 ohm speaker across 2 red wires coming from 9 pin molex connector on game control board.

NOTE: DO NOT LET SPEAKER LEADS TOUCH GROUND.

- 7. Push 5 VOLT switch to ON.
- 8. Push POWER switch to ON.
- 9. Push COIN switch once.
- Push START 1 switch once. 10.

RRP is steering control.

RLP is accelerator control.

SL6 is shift (Push down for low gear, up for high gear.)

12. RESET is START 2.

CONTROLS are:

11.

-WARNINGplease read instructions before using this card