

Electronics Division
Box 1246
1501 Webster Street
Dayton, Ohio 45401
Telephone (513) 223-8161

Operating Instructions

For Model __

263A

M-79 AMBUSH

Ranteck

	32	SL2				START 2			SR2			=	5 V
LLP	SL1	x SL5	2T3	LAP	×	X START 1	ALP	SR1	x SR5	SA3	AAP	ON	OF
x	×	x SL4	*	x	x	×	x	x	X SR4	x	×		
	SL6	×	SL7			COIN		SR 6	×	SR7		PO	WER
	×		A.			×		х		×	x	ÖN	OFF

- 1. Insert 263A card into program "A" connector, number side up.
- 2. Connect the 4 Molex connectors to the M-79 AMBUSH game board. Both boards must be connected together with the 25 pin ribbon cable used in the game.
- 3. Connect an ungrounded speaker to the speaker leads.
- 4. NOTICE!!! DO NOT turn on the 5V supply, as the test fixture and/or program card will be damaged!
- 5. Slide the POWER switch to "ON".

6.	GUN A	GUN B		
	SL-1	Gun Position	SR-1	
	SL-2	Gun Position	SR-2	
	SL-3	Gun Position	SR-3	
	SL-4	Gun Position	SR-4	
	SL-6	Gun Position	SR-6	
	SL-5	FIRE	SR-5	